



Mastercool[®] Inc.
"World Class Quality"

**Test Equipment
Depot**
1-800-517-8431


99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com

30 LB. AND 50 LB. DOT-APPROVED RECOVERY CYLINDERS

Features:

- Powder coated cylinder for high gloss, durable finish
- Y-valve for liquid/vapor
- 3/4" NPT opening accepts 80% fill float switch shut-off device
- 1/4" opening for air purge valve
- Collar design for ease of handling
- Reusable and conforms to DOT-4BA400 specifications and ARI guidelines
- Australian Approved and TC Canadian (CAN/CSA-B339-02) Approved
- Pre-charged cylinder provides a clean, dry interior
- Storage and transport of recovered refrigerant gases
- Valve & Float Switch UL Listed



Float Switch



3-Pin Brad Harrison

	30 lb.						50 lb.					
Model	62010 without float switch	62011 with float switch	62012 with float switch & NCG Port	64010 without float switch	67010 with float switch	67011 with float switch	63010 without float switch	65010 with float switch	66010 without float switch	66011 with float switch	66012 with float switch & NCG Port	63010-AUS without float switch (Australian standard)
Connection	1/4" FL-M (7/16-20)			1/2" ACME		1/2" ACME	1/4" FL-M (7/16-20)		1/2" ACME		1/2" ACME	
Size (w x h)	9.125" x 17.52"			9.125" x 17.52"		9.125" x 17.52"	12.25" x 18.78"		12.25" x 18.78"		12.25" x 18.78"	
Tare Weight	17.99 LB			17.99 LB		17.99 LB	28.71 LB		28.71 LB		28.71 LB	
Standard Specification	DOT - 4BA400 CAN/CSA-B339-02			DOT - 4BA400 CAN/CSA-B339-02		DOT - 4BA400 CAN/CSA-B339-02	DOT - 4BA400 CAN/CSA-B339-02		DOT - 4BA400 CAN/CSA-B339-02		DOT - 4BA400	
Nominal Water Capacity	>26.2 LB / 11.9 L			>26.2 LB / 11.9 L		>26.2 LB / 11.9 L	>47.7 LB / 21.6L		>47.7 LB / 21.6L		>47.7 LB / 21.6L	
Service Pressure	400 PSI / 2.7 MPa			400 PSI / 2.7 MPa		400 PSI / 2.7 MPa	400 PSI / 2.7 MPa		400 PSI / 2.7 MPa		400 PSI / 2.7 MPa	
Tank Test Pressure	800 PSI / 5.5 MPa			800 PSI / 5.5 MPa		800 PSI / 5.5 MPa	800 PSI / 5.5 MPa		800 PSI / 5.5 MPa		800 PSI / 5.5 MPa	
Relief Valve Pressure	600 PSI / 4.1 MPa			600 PSI / 4.1 MPa		600 PSI / 4.1 MPa	600 PSI / 4.1 MPa		600 PSI / 4.1 MPa		600 PSI / 4.1 MPa	
Air Tightness Test Pressure	400 PSI / 2.7 MPa			400 PSI / 2.7 MPa		400 PSI / 2.7 MPa	400 PSI / 2.7 MPa		400 PSI / 2.7 MPa		400 PSI / 2.7 MPa	
Body Material	HP295			HP295		HP295	HP325 or HP345		HP325 or HP345		HP325 or HP345	
Color	yellow/gray			blue		yellow/blue	yellow/gray		yellow/gray		white	